


Polishing sticks, square
Ordering example: P4SV 0606.070 SIC 80 hard

Packing unit:

10 pcs. per type

Further dimensions on request

 All items are available within a few days
ex-intermediate stock.

Description	H mm	B mm	L mm			recommended for												
P4SV 0606.070	6	6	70			1	2	3	4	5	6	7						▲
P4SV 0606.140	6	6	140			1	2	3	4	5	6	7					▲	
P4SV 1010.070	10	10	70			1	2	3	4	5	6	7					▲	
P4SV 1010.140	10	10	140			1	2	3	4	5	6	7					▲	
P4SV 1010.210	10	10	210			1	2	3	4	5	6	7					▲	
P4SV 1212.140	12	12	140			1	2	3	4	5	6	7					▲	
P4SV 1212.210	12	12	210			1	2	3	4	5	6	7					▲	
P4SV 1515.070	15	15	70			1	2	3	4	5	6	7					▲	
P4SV 1515.140	15	15	140			1	2	3	4	5	6	7					▲	
P4SV 1515.210	15	15	210			1	2	3	4	5	6	7					▲	
P4SV 1515.280	15	15	280			1	2	3	4	5	6	7					▲	

Material classification

1 STEELS AND CAST STEELS

Rm up to 800 N/mm²

- common structural steels
- free cutting steels
- case hardened steels
- fine grained structural steels
- extruded steels
- toughened structural steels
- boiler plate
- nitrided steels
- cast steels
- heat treated steels
- heat resistant structural steels

2 ALLOYED, TEMPERED STEELS

Rm 800 up to 1200 N/mm²

- case hardened steels
- spring steels
- fine grained structural steels
- nitrided steels
- heat treated steels
- wear resistant steels
- bearing steels

3 TOOL STEELS Rm up to 1300 N/mm²

- 60 - 65 HRC
- high-speed steels
- non-alloyed tool steels
- cold working tool steels
- hot working tool steels

4 RUST, ACID AND HEAT RESISTANT STEELS AND CAST STEELS

- austenitic
- ferritic
- ferritic-austenitic
- heat-resistant
- martensitic
- stainless, sulphurized

5 CAST IRON

6 ALUMINIUM, MAGNESIUM AND COPPER ALLOYS

- over 300 HB
- 200-300 HB
- up to 200 HB
- over 15% Si
- 10-15% Si
- 0,5-10% Si
- below 0,5% Si

7 TITANIUM AND NICKEL ALLOYS

- Rm 900 up to 1500 N/mm²
- Rm up to 900 N/mm²

8 PLASTICS, WOOD, RUBBER

9 GLASS / CARBIDES

10 STONE / TILES / GAS CEMENT

11 CONCRETE / REINFORCED CONCRETE

12 CERAMIC / FLOOR TILES

13 MARBLE

14 GRANITE

15 FRESHLY POURED CONCRETE

16 ASPHALT

● best suitable

○ suitable

■ delivery ex-stock

▲ delivery on request

Ⓢ regrind service, please enquire

Safety Symbols

(Depending on the product these symbols may vary)



Wear eye protection



Wear hearing protection



Wear a respirator



Read the instructions



Wear gloves



Only permitted with a back-up pad



Not permitted for wet grinding



Not permitted for face grinding



Do not use if damaged



Do not use for freehand cutting