


**LWL, Flap rolls of abrasive cloth with thread**
*Ordering example: A2280100501060*

**Packing unit:**

2 pcs. per type

NK = reg. Aluminium Oxide

Suitable for controlled angle grinders.

Description	Grits	d <sub>1</sub> mm	b mm	Thread	n recom. (1/min)	n max. (1/min)	Product-Number	recommended for		
LWL 100050	NK 60	100	50	M 14	3.700	6.000	A2280100501060	<span style="border: 1px solid red; border-radius: 50%; padding: 2px;">1</span> <span style="border: 1px solid red; border-radius: 50%; padding: 2px;">2</span> <span style="border: 1px solid red; border-radius: 50%; padding: 2px;">3</span> <span style="border: 1px solid red; border-radius: 50%; padding: 2px;">4</span> <span style="border: 1px solid red; border-radius: 50%; padding: 2px;">5</span> <span style="border: 1px solid red; border-radius: 50%; padding: 2px;">6</span> <span style="border: 1px solid red; border-radius: 50%; padding: 2px;">7</span> <span style="border: 1px solid red; border-radius: 50%; padding: 2px;">8</span>	■	<b>NEW</b>
LWL 100050	NK 80	100	50	M 14	3.700	6.000	A2280100501080	<span style="border: 1px solid red; border-radius: 50%; padding: 2px;">1</span> <span style="border: 1px solid red; border-radius: 50%; padding: 2px;">2</span> <span style="border: 1px solid red; border-radius: 50%; padding: 2px;">3</span> <span style="border: 1px solid red; border-radius: 50%; padding: 2px;">4</span> <span style="border: 1px solid red; border-radius: 50%; padding: 2px;">5</span> <span style="border: 1px solid red; border-radius: 50%; padding: 2px;">6</span> <span style="border: 1px solid red; border-radius: 50%; padding: 2px;">7</span> <span style="border: 1px solid red; border-radius: 50%; padding: 2px;">8</span>	■	<b>NEW</b>

## Material classification

### 1 STEELS AND CAST STEELS

Rm up to 800 N/mm<sup>2</sup>

- common structural steels
- free cutting steels
- case hardened steels
- fine grained structural steels
- extruded steels
- toughened structural steels
- boiler plate
- nitrided steels
- cast steels
- heat treated steels
- heat resistant structural steels

### 2 ALLOYED, TEMPERED STEELS

Rm 800 up to 1200 N/mm<sup>2</sup>

- case hardened steels
- spring steels
- fine grained structural steels
- nitrided steels
- heat treated steels
- wear resistant steels
- bearing steels

### 3 TOOL STEELS Rm up to 1300 N/mm<sup>2</sup>

- 60 - 65 HRC
- high-speed steels
- non-alloyed tool steels
- cold working tool steels
- hot working tool steels

### 4 RUST, ACID AND HEAT RESISTANT STEELS AND CAST STEELS

- austenitic
- ferritic
- ferritic-austenitic
- heat-resistant
- martensitic
- stainless, sulphurized

### 5 CAST IRON

### 6 ALUMINIUM, MAGNESIUM AND COPPER ALLOYS

- over 300 HB
- 200-300 HB
- up to 200 HB
- over 15% Si
- 10-15% Si
- 0,5-10% Si
- below 0,5% Si

### 7 TITANIUM AND NICKEL ALLOYS

- Rm 900 up to 1500 N/mm<sup>2</sup>
- Rm up to 900 N/mm<sup>2</sup>

### 8 PLASTICS, WOOD, RUBBER

### 9 GLASS / CARBIDES

### 10 STONE / TILES / GAS CEMENT

### 11 CONCRETE / REINFORCED CONCRETE

### 12 CERAMIC / FLOOR TILES

### 13 MARBLE

### 14 GRANITE

### 15 FRESHLY POURED CONCRETE

### 16 ASPHALT

● best suitable

○ suitable

■ delivery ex-stock

▲ delivery on request

Ⓢ regrind service, please enquire

## Safety Symbols

(Depending on the product these symbols may vary)



Wear eye protection



Wear hearing protection



Wear a respirator



Read the instructions



Wear gloves



Only permitted with a back-up pad



Not permitted for wet grinding



Not permitted for face grinding



Do not use if damaged



Do not use for freehand cutting