

**SLB, Sheets of abrasive cloth**
*Ordering example: A3825230280040*

**Packing unit:**

50 pcs. per type

NK = reg. Aluminium Oxide

Description	Quality	wide mm	long mm	Product-Number	recommended for	
SLB 230280	NK 40	230	280	A3825230280040	① ② ③ ④ ⑤ ⑥ ⑦ ⑧	■
SLB 230280	NK 60	230	280	A3825230280060	① ② ③ ④ ⑤ ⑥ ⑦ ⑧	■
SLB 230280	NK 80	230	280	A3825230280080	① ② ③ ④ ⑤ ⑥ ⑦ ⑧	■
SLB 230280	NK 100	230	280	A3825230280100	① ② ③ ④ ⑤ ⑥ ⑦ ⑧	■
SLB 230280	NK 120	230	280	A3825230280120	① ② ③ ④ ⑤ ⑥ ⑦ ⑧	■
SLB 230280	NK 150	230	280	A3825230280150	① ② ③ ④ ⑤ ⑥ ⑦ ⑧	■
SLB 230280	NK 180	230	280	A3825230280180	① ② ③ ④ ⑤ ⑥ ⑦ ⑧	■
SLB 230280	NK 220	230	280	A3825230280220	① ② ③ ④ ⑤ ⑥ ⑦ ⑧	■
SLB 230280	NK 240	230	280	A3825230280240	① ② ③ ④ ⑤ ⑥ ⑦ ⑧	■
SLB 230280	NK 320	230	280	A3825230280320	① ② ③ ④ ⑤ ⑥ ⑦ ⑧	■
SLB 230280	NK 400	230	280	A3825230280400	① ② ③ ④ ⑤ ⑥ ⑦ ⑧	■
SLB 230280	NK 999	230	280	A3825230280999	① ② ③ ④ ⑤ ⑥ ⑦ ⑧	■

The LUKAS-sheets of abrasive cloth with optimum abrasive properties will enable you to achieve outstanding results with your manual grinding applications.

## Material classification

### 1 STEELS AND CAST STEELS

Rm up to 800 N/mm<sup>2</sup>

- common structural steels
- free cutting steels
- case hardened steels
- fine grained structural steels
- extruded steels
- toughened structural steels
- boiler plate
- nitrided steels
- cast steels
- heat treated steels
- heat resistant structural steels

### 2 ALLOYED, TEMPERED STEELS

Rm 800 up to 1200 N/mm<sup>2</sup>

- case hardened steels
- spring steels
- fine grained structural steels
- nitrided steels
- heat treated steels
- wear resistant steels
- bearing steels

### 3 TOOL STEELS Rm up to 1300 N/mm<sup>2</sup>

- 60 - 65 HRC
- high-speed steels
- non-alloyed tool steels
- cold working tool steels
- hot working tool steels

### 4 RUST, ACID AND HEAT RESISTANT STEELS AND CAST STEELS

- austenitic
- ferritic
- ferritic-austenitic
- heat-resistant
- martensitic
- stainless, sulphurized

### 5 CAST IRON

### 6 ALUMINIUM, MAGNESIUM AND COPPER ALLOYS

- over 300 HB
- 200-300 HB
- up to 200 HB
- over 15% Si
- 10-15% Si
- 0,5-10% Si
- below 0,5% Si

### 7 TITANIUM AND NICKEL ALLOYS

- Rm 900 up to 1500 N/mm<sup>2</sup>
- Rm up to 900 N/mm<sup>2</sup>

### 8 PLASTICS, WOOD, RUBBER

### 9 GLASS / CARBIDES

### 10 STONE / TILES / GAS CEMENT

### 11 CONCRETE / REINFORCED CONCRETE

### 12 CERAMIC / FLOOR TILES

### 13 MARBLE

### 14 GRANITE

### 15 FRESHLY POURED CONCRETE

### 16 ASPHALT

● best suitable

○ suitable

■ delivery ex-stock

▲ delivery on request

Ⓢ regrind service, please enquire

## Safety Symbols

(Depending on the product these symbols may vary)



Wear eye protection



Wear hearing protection



Wear a respirator



Read the instructions



Wear gloves



Only permitted with a back-up pad



Not permitted for wet grinding



Not permitted for face grinding



Do not use if damaged



Do not use for freehand cutting